



T3A-IE3 132M2-6 5,5kW 400/690V 50Hz , . # TB37655051T001

**DATASHEET**

50Hz |

Frame type:	aluminium	Connection:	Δ/Y
Model:	T3A-IE3	Run Capacitor:	
Output:	5,5 kW	Start Capacitor:	
Rated voltage:	400/690V	Rotor voltage:	
Frame:	132 mm	Rotor connection:	
Poles:	6	Rotor current:	
Frequency:	50 Hz	No load current:	
Rated speed:	975 RPM	Insulation class:	F
Rated current:	12,7/7,4 A	Temp. rise:	80 K
Locked rotor current(Ia/In):	740%	Service factor:	1
Locked rotor torque(Ma/Mn):	290%	Duty:	S1
Breakdown torque(Ma/Mn):	350%	Amb. temp.:	-20~40 °C
Mounting:	B3	Altitude:	1000 m
Noise level:	68 dB	Protection:	IP55
Approx. weight:	55,7 kg	Cooling:	IC411
Mom. of inertia:	0,0539871 kg/m2	Vibration:	2,2 mm/s
Slip:	2,5%	Dir. rotation:	BOTH
Rated torque:	53,8 Nm	Starting method:	DIRECT ON LINE
		Coupling:	DIRECT
		Load type:	PARABOLIC CURVE

**PERFORMANCE**

<b>Output</b>	<b>50%</b>	<b>75%</b>	<b>100%</b>
Efficiency(%):	87,1	88,3	88
Power factor:			0,71

**BEARING**

<b>Bearing</b>	<b>NDE</b>	<b>DE</b>
	6208 2RZ	6308 2RZ
	C3	C3

Regreasing int(h):  
 Grease amount(g):  
 Grease polyrexEM:

**STANDARDS**

Specification:	IEC60034-1/GB755
Test:	IEC60034-2/GB/T1032
Noise	IEC60034-9/GB10069.3
Vibration:	IEC60034-14/GB10068

**ACCESSORIES**

PTC 150°C

There may be differences between rating plate and calculated values