

POOL LIGHTING



410	LIGHTS NEW LEGISLATIONS	431	HALOGEN LAMPS AND HALOGEN LIGHTING
412	LED LIGHTING - LUMIPLUS	433	NICHES
412	LEDs selection guide	435	TRANSFORMERS AND ACCESSORIES
414	LED LumiPlus Flexi	438	AQUARMONY UNDERWATER MUSIC SYSTEM
419	LED LumiPlus Flexi Mini	440	ZODIAC LED NL
420	LED LumiPlus Design		
421	LED LumiPlus Lamps PAR 56		
422	LED LumiPlus Mini V3		
423	LED LumiPlus Mini V2		
424	LED LumiPlus Micro		
426	LED lighting – Control systems		
430	Aquasphere – Other LED lights		

New EU regulation*

from 1st September 2021

According to the eco-design regulation, the swimming pool halogen lights can no longer be sold in the European Union market



POOL
LIGHTING

2021 LEDs ONLY



We are your LED's best partner

With our LED solutions for swimming pools, we'll make it easy for you and your customers



MADE IN EUROPE

100% production in our own facilities



QUALITY CONTROL

360° continuous control from suppliers
ISO certifications to finished products



BUILT BY POOL EXPERTS

More than 15 years of R&D experience to
design, inject and test watertight solutions

*EU Regulation 2019/2020 (Ecodesign requirements for light sources), halogen lights for swimming pools can no longer be sold in the EU countries. This also applies to the United Kingdom and Qatar.

FLUIDRA

Energy efficiency

New European regulation of energy labeling for lamps and projectors




NEW ENERGY EFFICIENCY LABEL FOR LIGHTING


The European Union launches the European Regulation EU 2019/2015 on new energy efficiency labeling in lamps and projectors that starts on September 1st, 2021 and repeals the European Regulation EU 874/2012.

The new Energy Efficiency label allows:

- Providing more information to the installer and customer. Thanks to the new QR code will access the European EPREL base, where the characteristics of the product are available.
- Carrying out a new energy classification promotes evolution of lighting technology.
- Greater control of products manufactured in the EU, with the QR code.



New label



Old label

The new classification must be marked on the unit packagings with the label, and in catalogs and product data sheets with the symbol below.



LEDs selection guide



		Projectors							Lamps			
		Commercial pools		Residential pools			Stairs	SPAS	Commercial pools	Residential pools		
		LumiPlus Design	LumiPlus Flexi V2	LumiPlus Flexi V1	PAR56 & Flat	LumiPlus FlexiMini V2	LumiPlus FlexiMini V1	LumiPlus Micro	LumiPlus PAR56 V2	LumiPlus PAR56 V1 (2)	Lamps PAR56 (2)	
Brand												
Lifespan (h)		L70 50000h	L70 50000h	L70 50000h	L70 25000h	L70 50000h	L70 50000h	L70 50000h	L70 50000h	L70 50000h	L70 50000h	L70 25000h
Warranty (years)		3	3	3	2	3	3	2	3	3	3	2
Decorative ring		Stainless Steel effect White	Stainless Steel White Anthracite Light grey Beige			White	Stainless Steel White Anthracite Light grey Beige		Stainless Steel White	-	-	-
Type of installation		Niche Ø180 mm	Niche Ø180 mm up to 230 mm (PAR56) Surface mounted Inlet or nozzle			Niche Ø230 mm (PAR56) Surface mounted	Mini niche Nozzles Pipes		Ø50 mm pipe 1 1/4 thread	PAR56 Projector		
RGB	Watts	AC	32	43	22	15	7.6	3.8	4	48	22	15
	Lumens		2544	2544	1100	900	600	300	186	2544	1100	900
	Efficiency											
	Control options	Control	LumiPlus Top LumiPlus App LumiPlus DMX 		LumiPlus ECO LumiPlus Top LumiPlus App 	Wireless Control Motion	RC	(a) LumiPlus Top LumiPlus App LumiPlus DMX 	(a) LumiPlus Eco LumiPlus Top LumiPlus App 	LumiPlus Top LumiPlus App LumiPlus DMX 	LumiPlus Top LumiPlus App LumiPlus DMX 	(a) LumiPlus ECO LumiPlus Top LumiPlus App
							(b) Wireless Control Motion	(b) Wireless Control Motion			(b) Wireless control Motion	
White	Watts	DC High efficiency			8.7							
		DC		32	14		6.8	3		32	14	
		AC	45	32	14.5	11.5	7.2	3.5	4		14.5	11.5
	Lumens		4320	4320	1485	1300	900	450	315	4320	1485	1300
Efficiency	DC ⁽¹⁾ High efficiency											
	DC ⁽¹⁾											
	AC											

* Compatible with ABS niches.
 (1) DC - power supply included.
 (2) AC lamp direct retrofit with 300 W halogen lamps.




AstralPool LumiPlus is the most extensive family in the market of underwater spotlights for public, commercial and residential pools.

The entire LumiPlus range is made of high-quality LEDs and electronic components, and is manufactured entirely in the EU to European quality standards.

The AstralPool LumiPlus family delivers:

- Greater energy efficiency.
- High performance projectors with top quality lighting (TQL) technology.
- Enhanced energy efficiency in pools thanks to the use of LumiPlus DC lamps and projectors run from a direct current power source (24 V DC).
- Great control over the range with the inclusion of the Internet of Pools (IoP) concept by Fluidra Connect.
- IP68 protection rating.
- L70 50000 hours lifespan.

The most comprehensive range for every type of pool



NEW
2022

PROJECTOR


LumiPlus Flexi

The LED solution that adapts to every type of pool

NEW
2022

High efficiency Flexi lamp

The most efficient solution 170 lm/W



The LumiPlus projectors, FlexiNiche, FlexiSlim and FlexiRapid, are characterised by their more stylish finish and their great adaptability to any type of new-build or existing pool, whether a liner or concrete pool, that can be fitted to niches on the surface or in bushings.



WHITE ANTHRACITE GREY BEIGE LIGHT GREY STAINLESS STEEL

“AstralPool’s LumiPlus Flexi system delivers top flexibility”



POOL
LIGHTING

PROJECTOR

LumiPlus Flexi

The LED solution that adapts to all types of pool



The family of LumiPlus Flexi spotlights – FlexiNiche, FlexiSlim and FlexiRapid – is characterized by its great adaptability to any type of new-build or existing pool, whether a liner or concrete pool, that can be fitted to niches, on the surface or in bushings. The LumiPlus Flexi system delivers top flexibility.

Versions V1 and V2 are ideal for residential pools and public/hotel pools, respectively.

LumiPlus Flexi is the perfect solution for your pool that lets you choose:

1. The color of the light.
2. The mounting system.

3. The faceplate color that best matches your pool, between white, beige, Light grey, anthracite grey and stainless steel, this one only for the FlexiNiche version.

The FlexiNiche version with his unique system of screws can adapt to any niche from diameter 180 up to 230 mm.

FlexiSlim version is compatible with the brackets for Flat, Extraflat and Slim Projectors by AstralPool.

FlexiRapid is compatible with any bushing with 1 1/2" internal thread.




Dimensions


LumiPlus FlexiNiche		LumiPlus FlexiSlim	LumiPlus FlexiRapid
Niche Ø 180-230 mm		Walls	Inlets
ABS	Full stainless steel		

Dimensions

Spotlight LumiPlus Flexi



How to install them?



Point of light features

	Color of lamp	Watts	Color temperature	Control system	Efficiency
Residential V1 WHITE : 1485 lm / RGB : 1100 lm AC - 12V AC / DC - 24V DC	White AC	14.5 W (20VA)	5 700K	ON / OFF	E
	Warm White AC	14.5 W (20VA)	3 000K	ON / OFF	E
	White DC	14 W	5 700K	ON / OFF	E
	Warm White DC	14 W	3 000K	ON / OFF	E
	White DC high efficiency	8.7 W	5 700K	ON / OFF	B
	RGB AC	22 W (29 VA)	-	LumiPlus ECO / LumiPlus Top / Fluidra Connect / WIFI LED App	G
	RGB WIR AC	22 W (29 VA)	-	Wireless Control Motion	G
Public/Hotel V2 WHITE : 4320 lm / RGB : 2544 lm AC - 12V AC / DC - 24V DC	White AC	32W (42VA)	5 700K	ON / OFF	D
	Warm White AC	32W (42VA)	3 000K	ON / OFF	D
	White DC	32 W	5 700K	ON / OFF	D
	Warm White DC	32 W	3 000K	ON / OFF	D
	RGB AC	43W (54VA)	-	LumiPlus ECO / LumiPlus Top / Fluidra Connect / WIFI LED App	G
	DMX RGB AC	43W (54VA)	-	LumiPlus RGB DMX	G

*Sea water-proof. ABS versions.
AC - Alternating current. DC - Direct current. DC versions are delivered with power pack.



The models with RGB light are compatible with Fluidra Connect.

LumiPlus Flexi projectors

Components required to install a LumiPlus Flexi




Choose amongst the components according to your requirements:

- New-build pools - FlexiNiche or FlexiRapid: 1+2+3
- New-build pools - FlexiSlim: 1+3
- Replacement without changing niche: 1+3


LumiPlus Flexi is made up of 3 components

1




Spotlight

2





Niche

3



Decorative ring



The 3 components are required for the proper installation of FlexiNiche and FlexiRapid.

1 Spotlight		Code	Code
		V1	V2
	White AC LumiPlus Flexi spotlight	71200	71233
	Warm White AC LumiPlus Flexi spotlight	71200WW	71233WW
	White DC LumiPlus Flexi spotlight	71201	71202
	White DC LumiPlus Flexi spotlight High Efficiency	71236	
	Warm White DC LumiPlus Flexi spotlight	71201WW	71202WW
	RGB AC LumiPlus Flexi spotlight ⁽¹⁾	71203	71204
	Wireless AC LumiPlus Flexi spotlight ⁽²⁾	71205	
	Wireless AC 1 PL LumiPlus Flexi spotlight + 1 Control Motion ⁽²⁾	71206	
	Wireless AC 2 PL LumiPlus Flexi spotlight + 1 Control Motion ⁽²⁾	71207	
	RGB DMX AC LumiPlus Flexi spotlight ⁽¹⁾		71208

All spotlights come with a 2.5 m power cable. Power cables of 5 m, 10 m and 15 m available on request.

(1) Choose the most suitable control system (see control systems section).




(2) Compatible with ABS trim solutions.

2 Installation		Code	Code
		Niche Ø180	Niche Ø230
	Niches (*)		
	Niche in ABS for concrete pools	59813	00349
	Niche S.S. for concrete pools /prefabricated pools		54102 / 54103
	Niche in ABS for prefabricated pools with inserts	59814	00364 / 17805
	Niche in ABS for prefabricated pools without inserts	59815	28887 / 72261
	Niche in ABS for panel pools with inserts / without inserts		23671 / 23670
	Inlet		
	Inlet for concrete pools with 1 1/2" threaded Ø63 PN-6 piping		35418
	Inlet for concrete pools with 1 1/2" threaded Ø63 PN-10 piping		35421
	Inlet for liner prefabricated pools with 1 1/2" thread		27084
	Inlet for polyester prefabricated pools		38805

Other Ø230 and Ø180 niches also available (see catalogue).

For FlexiSlim version installed in concrete + liner pools, Kit 71234 should be used to complete installation (not delivered with).

* Suitable to use ABS niches with Flexi ABS decorative ring.


3 Decorative ring with fitting		Code
	FLEXINICHE	
	White	71209
	Beige	71209CL090
	Light Grey	71209CL129
	Anthracite grey	71209CL144
	Stainless steel AISI 316-L embellisher with ABS body	71209CLSS
	Full Stainless Steel AISI 316-L	73440
	FLEXISLIM	
	White	71210
	Beige	71210CL090
	Light Grey	71210CL129
	Anthracite grey	71210CL144
	FLEXIRAPID	
	White	71211
	Beige	71211CL090
	Light Grey	71211CL129
	Anthracite grey	71211CL144

KITS : DECORATIVE RING + SPOTLIGHT		Code	Code
		White AC 	White DC
	FlexiNiche: White decorative ring + white spotlight	71212	71213
	FlexiSlim: White decorative ring + white spotlight	71214	71215
	FlexiRapid: White decorative ring + white spotlight	71216	71217
	FlexiNiche : Full SS Projector body + white spotlight	73442	73441

AC - Alternating current DC - Direct current



LUMIPLUS FLEXIMINI COMPACT DESIGN. MAXI-CUSTOMIZATION.




THE PERFECT SIZE FOR A BETTER DESIGN.

LumiPlus FlexiMini is a compact LED solution in line with current design trends for residential pools. It combines perfectly with LumiPlus Flexi range.



SIMPLIFIED INSTALLATION.

LumiPlus FlexiMini provides one point of light common to all installation methods. Thanks to its simplified connection compatibility with each construction mode, LumiPlus FlexiMini enables easy installation and retrofit with most of the lightings on the market.



MAXI-CUSTOMIZATION FOR EVERYONE'S STYLE.

LumiPlus FlexiMini offers a customizable lighting installation with the desired lumens (2 levels for stairs and basin), with any connection mode (nozzles, tube, well conduits, niche) and 5 color options to create a unique lighting experience for the pool owner.

LumiPlus FlexiMini

Compact design. Maxi customization.



The LumiPlus Flexi Mini projector is an underwater projector with reduced dimensions that stands out for its ease and flexibility of installation, being compatible with the Mini V2 and V3 niches, 1 1/2" internal thread nozzles, 63mm or 2" cable glands, pipes D63 PN6 and PN10 or D50 PN10 pipes. Its configuration is carried out in three steps in new pools. You need to choose :

- 1.- The spotlight
- 2.- One of the 4 models of decorative ring: niche; nozzle L; nozzle S; or, for pipe or wall bushings.

The decorative ring can be made of ABS in a white, light gray, anthracite gray or beige finish; or AISI- 316L stainless steel.

- 3.- The niche, the nozzle or the wall bushing for the installation.


When renovating swimming pools, you should only choose sections 1 and 2.

The point of light is available in two powers, V1 for lighting stairs and V2 for lighting the basin, and you can choose between white, warm white and RGB multicolor light. The RGB versions are compatible with ECO, TOP, Wireless, LumiPlus LED App, ModBUS (Connect) and DMX controls (see page 426-427).



Dimensions

Spotlight FlexiMini



Dimensions

LumiPlus FlexiMini Niche	LumiPlus FlexiMini Nozzles L		LumiPlus FlexiMini Nozzles S		LumiPlus FlexiMini pipes / wall conduits
Niche	Nozzle L 2"	Nozzle L 1 1/2"	Nozzle S 2"	Nozzle S 1 1/2"	Pipe Ø50 PN6 / P10 Wall conduit 2" / 1 1/2"
Compatible with niches 06967; 00369; 49828	Compatible with nozzles Ømax. 116 mm and depth between 0 and 10 mm		Compatible with nozzles Ømax. 91 mm and depth between 7 and 9 mm		

How to install them?

LumiPlus FlexiMini Niche	LumiPlus FlexiMini Nozzles L	LumiPlus FlexiMini Nozzles S	LumiPlus FlexiMini Pipes / Wall conduits

Spotlight features

	Color of lamp	Watts	Color temperature	Control system	Efficiency
Pool stairs FlexiMini V1 WHITE : 450 lm/ RGB : 300 lm AC - 12V AC / DC - 24V DC	White AC	3.5 W	5 700K	ON / OFF	D
	White DC	3 W	5 700K	ON / OFF	C
	Warm White AC	3.5 W	3 000K	ON / OFF	D
	Warm White DC	3 W	3 000K	ON / OFF	C
	RGB	3.8 W	-	LumiPlus ECO / LumiPlus Top / Fluidra Connect / WIFI LED App	F
	RGB Wireless (WIR)	4.3 W	-	1) Wireless Control Motion	G
Residential pool basin and stairs FlexiMini V2 WHITE : 900 lm/ RGB : 600 lm AC - 12V AC / DC - 24V DC	White AC	7.2 W	5 700K	ON / OFF	D
	White DC	6.8 W	5 700K	ON / OFF	D
	Warm White AC	7.2 W	3 000K	ON / OFF	D
	Warm White DC	6.8 W	3 000K	ON / OFF	D
	RGB	7.6 W	-	LumiPlus ECO / LumiPlus Top / Fluidra Connect / WIFI LED App	F
	RGB Wireless (WIR)	8 W	-	1) Wireless Control Motion	F
	Kit 3 RGB Wireless V2 (with RC)	8 W	-	1) Wireless Control Motion	F
	DMX	8 W	-	LumiPlus RGB DMX	F

*Sea water-proof. ABS versions.
AC - Alternating current. DC - Direct current. DC versions are delivered with power pack.
1) Maximum installation depth 40cm.



The models with RGB are compatible with Fluidra Connect.

LumiPlus FlexiMini


Components to install a LumiPlus FlexiMini projector



The LumiPlus Flexi Mini is a solution that allows maximum flexibility in terms of colors of the lights, lumens color of the visible parts and as well of the installation method.

LumiPlus FlexiMini is a compact LED solution in line with current design trends for residential pools. It combines perfectly with LumiPlus Flexi range.

Choose amongst the components according to your requirements:



1 Spotlight		Code
1.1 - LUMIPLUS FLEXIMINI V1 - IDEAL FOR STAIRS		
	White AC	74400
	White DC	74401
	Warm White AC	74400WW
	Warm White DC	74401WW
	RGB	74402
	RGB Wireless (WIR)	74403
1.2 - LUMIPLUS FLEXIMINI V2 - IDEAL FOR RESIDENTIAL POOL		
	White AC	74406
	White DC	74407
	Warm White AC	74406WW
	Warm White DC	74407WW
	RGB	74408
	RGB Wireless (WIR)	74404
	Kit 3 RGB Wireless V2 + 1 Control Motion	74405
	DMX	74409

Note: 2.5 m cable included

2 LumiPlus FlexiMini Decorative ring with fitting (Delivered with installation accessories)		Code
2.1 - DECORATIVE RING FOR MINI NICHEs		
	Decorative ring for Mini Niche in ABS color White	74392
	Decorative ring for Mini Niche in ABS color Beige	74392CL090
	Decorative ring for Mini Niche in ABS color Light grey	74392CL129
	Decorative ring for Mini Niche in ABS color Anthracite	74392CL144
	Decorative ring for Mini Niche in Stainless Steel A316-L with ABS body	74392CLSS
2.2 - DECORATIVE RING FOR NOZZLES L (LARGE)		
	Decorative ring for nozzle L in ABS color White	74393
	Decorative ring for nozzle L in ABS color Beige	74393CL090
	Decorative ring for nozzle L in ABS color Light grey	74393CL129
	Decorative ring for nozzle L in ABS color Anthracite	74393CL144
	Decorative ring for nozzle L in Stainless Steel A316-L with ABS body	74393CLSS
2.3 - DECORATIVE RING FOR NOZZLES S (SMALL)		
	Decorative ring for nozzle S in ABS color White	74394
	Decorative ring for nozzle S in ABS color Beige	74394CL090
	Decorative ring for nozzle S in ABS color Light grey	74394CL129
	Decorative ring for nozzle S in ABS color Anthracite	74394CL144
	Decorative ring for nozzle S in Stainless Steel A316-L with ABS body	74394CLSS
2.4 - DECORATIVE RING FOR PIPE		
	Decorative ring for pipe in ABS color White	74395
	Decorative ring for pipe in ABS color Beige	74395CL090
	Decorative ring for pipe in ABS color Light grey	74395CL129
	Decorative ring for pipe in ABS color Anthracite	74395CL144
	Decorative ring for pipe in Stainless Steel A316-L with ABS body	74395CLSS

3 Installation supports per type of pool that combines with the decorative rings	Type of pool	Option	2.1 Faceplate for niches	2.2 - Faceplate for nozzles L	2.3 - Faceplate for nozzles S	2.4 - Faceplate for Pipe
Concrete	Recommended		06967	56498	35418	15661
	Other possibilities		-	00295, 00298, 56498, 00300, 00301	53956, 35421	00322, 00323
Concrete + liner	Recommended		00369	59983	00338	-
	Other possibilities		-	00332, 17382	27084	-
Panels	Recommended		00369	00330	27084	-
	Other possibilities		-	17383, 00332, 56498, 56499	06481, 32450, 33092, 33091, 06498	-
Polyester	Recommended		49828	00330	74179	-
	Other possibilities		-	00332, 00334, 00336	38805, 06481, 06484, 32450, 32451	-

Installation accessories can be found in Pool shell equipment chapter on within lights chapter, Niches subchapter.

Projector Design



DESCRIPTION

The LumiPlus Design projector is a high power underwater projector that can be installed in 180mm diameter niches.

The decorative ring is available in Stainless Steel effect and Pure White finishes.

The light can be white, warm white, and RGB multi-color. The RGB versions are compatible with ECO, TOP, Wireless, LumiPlus LED App, ModBUS (Connect) and DMX controls (see codes in page 427).

LumiPlus monocolour white light lamps and projectors are also available in Warm White.



TECHNICAL FEATURES


		Projector Design				
Light Colour		White 	Stainless steel effect 	Consumption	Luminous flux	
	White 	59807	59805	32W (35VA)	4320 lm	
	RGB 	59803	59801	32W (42VA)	2544 lm	
	RGB DMX 	59811	59809	32W (42VA)	2544 lm	

Rated voltage: 12V AC. IPX8 protection. Includes 2.5 m H07RN-F 2x1.5 mm² cable.
Adaptor kit available for other niche types from diameter 180 to 190 mm. Code: 59818. It must always be installed underwater.

Niches for projector Design



TECHNICAL FEATURES

Niches			
Concrete pool	Prefabricated pools		Fixing kit for other niches
	With inserts	Without inserts	
59813 	59814	59815	59818*

Compatible with: LumiPlus FlexiNiche ABS and Stainless Steel and LumiPlus Design.
*Compatible with the majority of niches from Ø180 to Ø190 mm on the market (Hugo Lahme, MTS Productksts, Wibre...).



Fluidra Connect-compatible



Seawater-proof

LED LIGHTING - LUMIPLUS

LumiPlus lamps for PAR56 V2 projectors



DC PAR56 V2 lamp



How to replace a PAR 56 lamp?



DESCRIPTION




The RGB model is compatible with LumiPlus ECO, LumiPlus Top, LumiPlus LED APP and LumiPlus Modbus controls. The RGB DMX model requires the LumiPlus DMX 41107 modulator.

To correctly light a pool it is advisable to install a light from the LumiPlus V1 range every 20m² of water surface. This recommendation applies to pools light in colour with white light spotlights, but if there are RGB spotlights more should be fitted. In dark or stainless steel pools it is recommended to use more projectors per m².

TECHNICAL FEATURES

DC PAR56 V2 lamp			
Light Colour	Code	Consumption	Luminous flux
 White Warm white	 67516 	32W	4320 lm
	67516WW 		

Rated voltage: 24 V DC. Protection rating: IPX8. Includes 220V AC - 24 V DC power pack. Does not work with 220 V AC-12 V AC electromagnetic transformers. It must always be installed underwater.

PAR56 V2 lamp			
Light Colour	Code	Consumption	Luminous flux
 RGB  RGB DMX	 43411 	48W (64VA)	2544 lm
	45637 	48W (64VA)	2544 lm

Rated voltage: 24 V DC. Protection rating: IPX8. It must always be installed underwater.

LumiPlus lamps for PAR56 V1 projectors



DC PAR56 V1 lamp



How to replace a PAR 56 lamp?






DESCRIPTION

The RGB model is compatible with LumiPlus ECO, LumiPlus Top, LumiPlus LED APP and LumiPlus Modbus controls. The RGB DMX model requires the LumiPlus DMX 41107 modulator.

To correctly light a pool it is advisable to install a light from the LumiPlus V1 range every 20m² of water surface. This recommendation applies to pools light in colour with white light spotlights, but if there are RGB spotlights more should be fitted. In dark or stainless steel pools it is recommended to use more projectors per m².

TECHNICAL FEATURES

DC PAR56 V1 lamp			
Light Colour	Code	Consumption	Luminous flux
 White Warm white	 67515 	14W	1485 lm
	67515WW 		

Rated voltage: 24V DC. Protection rating: IPX8. Includes 220V AC - 24 V DC power pack. Does not work with 220 V AC-12 V AC electromagnetic transformers. It must always be installed underwater.

PAR56 V1 lamp			
Light Colour	Code	Consumption	Luminous flux
 White Warm white	 52596 	14,5W (20VA)	1485 lm
	52596WW 		
RGB 	 56001 	22W (29VA)	1100 lm

Rated Voltage: 12V AC. Protection: IPX8. It must always be installed underwater.

Wireless PAR56 V1 lamp

	1 lamp + 1 Control Motion	2 lamps + 1 Control Motion	1 lamp RGB 1.11 Wireless	Consumption per lamp	Luminous flux per lamp
  	59126 	59127 	59124 	22W (29VA)	1100 lm

Rated voltage: 12V AC. Protection rating: IPX8. It must always be installed underwater. The LumiPlus Control Motion is not waterproof.  Seawater-proof

LumiPlus MINI V3 projectors



DESCRIPTION

The LumiPlus Mini V3 projector is a compact underwater projector made entirely of high-quality plastic. Available in white, warm white, and multi-color RGB light. The RGB versions are compatible with ECO, TOP, LumiPlus LED App, ModBUS (Connect) and DMX controls (see page 426-427). You can choose between two types of decorative ring: pure white and stainless steel effect. There are three versions of this projector: concrete pool, prefabricated pool and SPA. LumiPlus monocolour white light lamps and projectors are also available in Warm White.

TECHNICAL FEATURES

MINI V3 projector

Light Colour		Decorative ring	Concrete	Prefabricated/Liner	SPAS	Consumption	Luminous flux
White	F	White	59979	69637	59981	4W (6VA)	315 lm
		Stainless steel effect	59980	69638	59982		
RGB	G	White	59971	69633	59973	4W (7VA)	186 lm
		Stainless steel effect	59972	69634	59974		
RGB DMX	G	White	59975	69635	59977	4W (4VA)	186 lm
		Stainless steel effect	59976	69636	59978		

Rated Voltage: 12V AC (RGB & White) 24V DC (RGB-DMX). IPX8 protection. 2.5 m H07RN-F 2 x 1 mm² cable. It must always be installed underwater.



Niches, nozzles and fittings

for LumiPlus MINI V3

TECHNICAL FEATURES

Niches for LumiPlus MINI V3

Description	Concrete pools				Prefabricated pools		
	Bushing / Tube ø63 PN-6 / PN-10	1½ threaded inlet Ø 63 PN-6 piping	1½ threaded inlet Ø 63 PN-10 piping	Nozzle with niche	Liner 1½" thread inlet	Fibreglass Nozzle with niche	Fibreglass Inlet
Code	62395	35418	35421	53956	27084	59983	38805



Fluidra Connect-compatible



Seawater-proof



Until end of stock

LumiPlus MINI V2 projectors



Snap-in MINI V2 projectors



DESCRIPTION











To correctly light a pool it is advisable to install a projector from the LumiPlus Mini V2 range every 5 m² of water surface. NB: recommendations valid for light coloured pools and white light projectors; oversize in RGB colours. In darker coloured pools or stainless steel pools, we recommend oversizing the proportion of projectors per m².

Projectors may be installed both in and out of the water. Niche according to model; not included and needed to finish the installation. The RGB model is compatible with LumiPlus ECO, LumiPlus Top, LumiPlus LED APP and LumiPlus Modbus controls. The RGB DMX model requires the LumiPlus DMX 52142 controller (see page 426-427).

LumiPlus monocolour white light lamps and projectors are also available in Warm White.





TECHNICAL FEATURES

Snap-in MINI V2 projector

Light Colour		Type of decorative ring		Consumption	Luminous flux
		White	S.S.		
White		52130 	52131 	4W (6VA)	315 lm
RGB 		52124 	52125 	4W (7VA)	186 lm
RGB DMX		52136 	52137 	4W (4VA)	186 lm











Rated Voltage: 12V AC (RGB & White) 24V DC (RGB-DMX). IPX8 protection. Includes 2.5 m H07RN-F 2x1.5 mm² cable. Compatible with a Ø63 bushing (code 15661) or snap-in mini niche from concrete pool code 53956 (not included).

MINI V2 projector for SPA

Light Colour		Type of decorative ring		Consumption	Luminous flux
		White	S.S.		
White		52132	52133	4W (6VA)	315 lm
RGB 		52126	52127	4W (7VA)	186 lm
RGB DMX		52138	52139	4W (4VA)	186 lm

Rated Voltage: 12V AC (RGB & White) 24V DC (RGB-DMX). IPX8 protection. Includes 2.5 m H07RN-F 2x1.5 mm² cable. Fastened between a threaded bolt and 2" nut.

MINI V2 projector for Mini Niche (light point)

Light Colour		Type of decorative ring		Consumption	Luminous flux
		White	S.S.		
White		52134 	52135 	4W (6VA)	315 lm
RGB 		52128 	52129 	4W (7VA)	186 lm
RGB DMX		52140 	52141 	4W (4VA)	186 lm

Rated Voltage: 12V AC (RGB & White) 24V DC (RGB-DMX). IPX8 protection. Includes 2.5 m H07RN-F 2x1.5 mm² cable. To complete the projector select the right niche for each swimming pool type (see page 433).

Color front plates for MINI V2 projectors

	Beige	Light grey	Anthracite
 Color front plate for Snap-in MINI V2 projector and MINI V2 projector for SPA and prefabricated pool	08554-0500CL090	08554-0500CL129	08554-0500CL144
 Color front plate for MINI V2 projector for Mini Niche (light point)	04582-0500CL090	04582-0500CL129	04582-0500CL144



Fluidra Connect-compatible



Untill end of stock

LumiPlus MICRO projectors



Snap-in MICRO projectors



DESCRIPTION






To correctly light a pool it is advisable to install a projector from the LumiPlus Micro range every 5 m² of water surface. NB: recommendations valid for light coloured pools and white light projectors; oversize in RGB colours. In darker coloured pools or stainless steel pools, we recommend oversizing the proportion of projectors per m².

LumiPlus monocolour white light lamps and projectors are also available in Warm White.

Projectors may be installed both in and out of the water. Niche according to model; not included and needed to finish the installation. The RGB model is compatible with LumiPlus ECO, LumiPlus Top, LumiPlus LED APP and LumiPlus Modbus controls. The RGB DMX model requires the LumiPlus DMX 52142 feed controller (see page 426-427).




TECHNICAL FEATURES

Snap-in MICRO projector

Light Colour	Type of decorative ring		Consumption	Luminous flux		
	White	S.S.				
	White		38814	38816	4W (6VA)	315 lm
	RGB 		64552	64553	4W (7VA)	186 lm
	RGB DMX		64557	64558	4W (4VA)	186 lm

Rated Voltage: 12V AC (RGB & White) 24V DC (RGB-DMX). IPX8 protection. Includes 2.5 m H07RN-F 2x1.5 mm² cable.

MICRO projector for SPA

Light Colour	Type of decorative ring		Consumption	Luminous flux		
	White	S.S.				
	White		40765	40766	4W (6VA)	315 lm
	RGB 		64554	64555	4W (7VA)	186 lm
	RGB DMX		64559	64560	4W (4VA)	186 lm

Rated Voltage: 12V AC (RGB & White) 24V DC (RGB-DMX). IPX8 protection. Includes 2.5 m H07RN-F 2x1.5 mm² cable. Fastened between a threaded bolt and 2" nut.



Outdoor lighting

Starlight portable lights




DESCRIPTION

Decorative lights for indoors and out and even for floating in the water. Includes a remote control for choosing one of the 16 different colours available. They work on low consumption LED technology and once the battery has been charged have a runtime of up to 20 hours. Starlight is water-resistant The charger is supplied with the product.








	Code	Standard Pack	Standard weight in kg	Standard volume in m ³
StarLight Altair Conical shape 290 x 320 mm	53937	1	3	0.050
StarLight Sirio Circle shape Ø 350 mm	53938	1	3	0.051
StarLight Vega Oval shape 350 x 270 mm	53939	1	3	0.051



Control systems

	System		Code	Description	Projectors
LumiPlus RGB ECO			32458	<p>The simplest and most economical colour change system.</p> <p>LumiPlus ECO is a push-button switch that allows 14 modes of operation: 7 fixed colours and 7 different colour sequences. Each time the push button is pressed, the colour or sequence will change. By pressing for several seconds, the light is white.</p> <p>The push button must be sized to withstand the power consumed by the number of lights in the facility. Maximum charge 700 VA. Must be connected in the transformer primary.</p>	Any LumiPlus RGB projector.
LumiPlus WIRELESS	LumiPlus Control Motion		59125	<p>Colour change CONTROL in your hand.</p> <p>The LumiPlus Control Motion remote control enables wireless projector control, directly offering on/off options, 12 colour changes, 8 sequence changes and sequence speed. It also detects movement, letting you activate colours and sequences by vertical and horizontal movements, respectively.</p> <p>Compatible with the LumiPlus Wireless range of projectors only. Can control 2 wireless projectors and 3 in FlexiMini</p>	Flexi (ABS body) V1 RGB Wireless PAR56 V1 RGB Wireless * Not compatible with stainless steel FlexiNiche projectors.
	LumiPlus Wireless Range Extender		64633	<p>Allows expansion of the signal that the LumiPlus Control Motion sends to the projectors with the wireless control system.</p> <p>Ideal for facilities whose architectural features or projectors installation makes it hard for the LumiPlus Control Motion signal to reach the wireless projectors properly.</p>	
LumiPlus RGB TOP			27818 + 41988	<p>The LumiPlus TOP system is a professional control of the color.</p> <p>System comprising the 27818 modulator and 41988 remote control that enables to control a large number of projectors. The modulator has an antenna with a 50m range to receive the signal from the remote control (bought separately).</p> <p>The LumiPlus TOP system enables:</p> <ul style="list-style-type: none"> Projector on/off action. Colour selection: 12 fixed colours available. Sequence selection: 8 sequences available. Sequence speed selection: 8 speeds available for each sequence. <p>Supplied separately. A total of 10 LumiPlus modulators can be synchronized.</p>	Any LumiPlus RGB projector.
LumiPlus LED APP LumiPlus WIFI	Existing installation		59131	<p>Control your pool lighting from your smartphone.</p> <p>App to check LumiPlus lights and projectors from an Android or iOS smartphone or tablet.</p> <p>Enables to control your LumiPlus lights or spotlights from your smartphone or tablet.</p>	Any LumiPlus RGB projector
	New installation		59132	<p>The LumiPlus app should only be installed as an additional feature to the LumiPlus Modulator. It offers a range of 12 colours and 8 sequences or colour change programs.</p> <p>Free app you can download directly from the following sites:</p> <p>Apple: www.lumiplusled-ios.astralpool.com Android: www.lumiplusled-android.astralpool.com</p> 	

Control systems

	System		Code	Description	Projectors
LumiPlus Modbus FLUIDRA CONNECT 				Control your pool lighting anywhere, anytime.	
	Existing installation		57434	<p>The Modbus protocol enables the control of the LumiPlus modulator. It can be used to switch the projectors on and off, change their colours and sequence speed and set the time for putting the projectors in sleep mode.</p> <p>Download the Fluidra Connect app for instant information about the state of your pool 365 days a year. Fluidra Direct is peace of mind, comfort and leisure. In addition to controlling projectors, LumiPlus lets you control the filtration, water treatment and more of your pool through the Modbus protocol.</p>	Any LumiPlus RGB projector
New installation		57435	<p>The LumiPlus Modbus should only be installed as an additional feature to the LumiPlus 27818 modulator for correct installation and operation.</p>		
LumiPlus RGB DMX	RGB DMX Modulator		41107	<p>DMX LED projector modulator/12V AC</p> <p>DMX receiver for the Flexi, PAR56, S-LIM and Design ranges.</p> <p>Receiving orders from the DMX controller (Astral DMX 74099 or Astral DMX Pro 74500) via the DMX bus and acting on the projectors that are connected.</p>	LumiPlus RGB-DMX projector
	RGB-DMX power pack		52142	<p>Product designed exclusively for use with V2 and V3 Mini LED and RGB DMX Micro projectors.</p> <p>The power pack can control up to 9 projectors, receiving orders from the system's DMX controller (Astral DMX 74099 or Astral DMX Pro 74500) via the DMX bus and acting on the projectors that are connected.</p> <p>The power pack has been designed to be used solely with DMX protocol and 24V DC DMX controllable parts from AstralPool.</p>	
	DMX controller		74099	<p>LumiPlus DMX System makes it possible to control lights individually or by groups.</p> <p>Users will have easy and intuitive full control over a projector or group of projectors.</p> <p>Main advantages / benefits:</p> <ul style="list-style-type: none"> Very accurate control over the lights: colour and dimming. Plug and play. Projectors can be operated independently or combined. Allows creating new light scenes. 	
	DMX PRO controller		74100	<p>LumiPlus DMX system does not require any additional wiring for projectors.</p> <p>Smartphone or tablet control via an app.</p>	

Did you know?

According to EN 2012/19/UE,
broken halogen lamps should be disposed in special recycling centers.

We do it for YOU



Fluidra is committed to the environment by using sustainable products and practices to protect future generations.

Did you know?

LED lamps power consumption is 30x lower than Halogen lamps* and **LEDs lifespan is 10x** more than Halogen lamps.

DO like 70% of pool builders
& CONTRIBUTE to the environment


Example of consumption in kW

1 pool with 2 projectors.

Usage : 4 months / 4 hours per day.

Price of kWh : 0.18 €.

Consumption per season



Power cost difference per season pays the price difference between halogen and LED lamps.

*Note : example taken Lamp PAR56 halogen 300 watts and a Lamp PAR56 11.5W , color white

Other LED solutions:

PAR56 projectors, PAR56 lamps and Flat projectors



PAR56 projectors



DESCRIPTION

PAR56 underwater lamp, improves energy efficiency compared to the traditional 300 W halogen PAR56 lamps. It must always be installed completely submerged. The lamps PAR56 are directly retrofittable with halogen 300 W lamps / projectors.

Lifespan of 25000 h.

The RGB lamp is controlled by a remote control, which is included, with a 2 m range and can control 2 lamps. The White lamp does not include remote control.

To correctly light a pool it is advisable to install a light from this range every 15 m² of water surface.

Note: this recommendation applies to pools light in color with white light spotlights, but if there are RGB spotlights more should be fitted. In dark pools it is recommended to use more projectors per m².

Projectors PAR56 needs a niche (see page 433) to complete the installation. Projector Flat to wall installations is delivered with the accessory to install in concrete and polyester pools. To complete the installation in panel pools needs spare part kit 24765-0500.

How to replace a PAR56 lamp?



TECHNICAL FEATURES

PAR56 projectors

	Light color	Embellisher	Code	Consumption	Luminous flux		
	White		White	74940	11.5W (18VA) NEW 2022	1300 lm	
			Beige	74940CL090			
			Light grey	74940CL129			
			Anthracite grey	74940CL144			
	RGB			White	71742	15 W (23 VA)	900 lm
			Beige	71742CL090			
			Light grey	71742CL129			
			Anthracite grey	71742CL144			

Must be connected to a 12VAC safety transformer. 2.5 m cable. IPX8 protection.

PAR56 lamps

	Light color	Code	Consumption	Luminous flux
	White	74939	11.5W (18VA) NEW 2022	1300 lm
	RGB	71740	15 W (23 VA)	900 lm

Must be connected to a 12VAC safety transformer. IPX8 protection.

Flat projectors

	Light color	Code	Consumption	Luminous flux
	White	74941	11.5W (18VA) NEW 2022	1300 lm
	RGB	71744	15 W (23 VA)	900 lm

Must be connected to a 12VAC safety transformer. 2.5 m cable. IPX8 protection.

HALOGEN LIGHTING

Standard light



According to UE Regulation 2019/2020, from September 1st, 2021 halogen cannot be sold anymore on the European Union market. This is also valid in other countries such as UK and Qatar.



DESCRIPTION

All plastic materials. PAR56 300W 12V AC halogen lamp.

For correct pool lighting, we recommend: one projector per 25-30 m² of pool area. This recommendation is valid for light coloured pools. For pools in dark colours or stainless steel, we recommend a higher proportion of projectors per m².

The projector must be always be submerged in water.

Projectors for installation in "standard" niche (included).

TECHNICAL FEATURES

Standard light

Type of pool	Cable 2x6 mm ² 2.5 m	Type of decorative ring Ø280 mm		Consumption	Niche included
		ABS	S.S.		
Concrete	Yes	07844	07843	300W (300 VA)	Yes
	No	07838	07837		
Prefabricated	Yes	07856	07855		
	No	07852	07851		

Rated voltage: 12 V AC. Protection rating: IPX8. Compatible with standard niches (included).

Global light



According to UE Regulation 2019/2020, from September 1st, 2021 halogen cannot be sold anymore on the European Union market. This is also valid in other countries such as UK and Qatar.



DESCRIPTION

Made of plastic with hardware and anchoring system also made of plastic. Suitable for sea water.

Model based on standard projector. PAR56 300W 12V AC halogen lamp.

For correct pool lighting, we recommend one projector per 25-30 m² of pool area. This recommendation is valid for light coloured pools. For pools in dark colours or stainless steel, we recommend a higher proportion of projectors per m².

The projector must be always be submerged in water.

Compatible with AstralPool niches (not included) or any niche available on the market with interior diameters ranging between 220 mm and 235 mm (e.g.: Standard model and PS model).


For full projector assembly, the niche must be purchased separately (see page 433).

TECHNICAL FEATURES

Global light

Type of pool	Cable 2x6 mm ² 2.5 m	Type of decorative ring Ø280 mm	Consumption	Niche included
		ABS		
All depending on the niche	Yes	52608 	300W (300 VA)	No

Rated voltage: 12 V AC. Protection rating: IPX8. Compatible with standard and PS niches (not included).



Seawater-proof

Mini light

According to UE Regulation 2019/2020, from September 1st, 2021 halogen cannot be sold anymore on the European Union market. This is also valid in other countries such as UK and Qatar.



Fast assembly Mini light

DESCRIPTION

Small underwater projector. GX-5.3 50W 12V AC aluminized halogen lamp.


For correct pool lighting, we recommend one projector per 10 m² of pool area. This recommendation is valid for light coloured pools. For pools in dark colours or stainless steel, we recommend a higher proportion of projectors per m².

The projector must be always be submerged in water.

Projectors for installation in bushings or niche, depending on model (not included). To complete the installation the right housing should be purchased for each type of pool (see page 433). This recommendation is valid for light coloured pools. For pools in dark colours or stainless steel, we recommend a higher proportion of projectors per m².


TECHNICAL FEATURES

Fast assembly Mini light

	Body	Type of decorative ring Ø96 mm		Consumption	Fixing
		ABS			
	Plastic	33708		50W (50 VA)	Ø63 wall conduit or Fast assembly Mini Niche
	Metal	33684			


Rated voltage: 12V AC. IPX8 protection. Includes 2.5 m H07RN-F 2 x 1.5 mm² cable. Compatible with a 63 bushing (code 15661) or snap-in mini niche (not included). Select the appropriate option for each pool (see page 433).

Mini light for Spa and prefabricated pool

	Body	Type of decorative ring Ø96 mm		Consumption	Fixing
		ABS	S.S.		
	Plastic	33709	36647	50W (50 VA)	Threaded body and 2" nut
	Metal	33685	36642		

Rated voltage: 12 V AC. Protection rating: IPX8. Includes 2.5-m H07RN-F 2 x 1.5 mm² cable.

Mini light for Mini Niche (Light spot)

	Body	Type of decorative ring Ø96 mm		Consumption	Fixing	Niche included
		ABS	S.S.			
	Plastic	49820	49821	50W (50 VA)	Mini niche	No
	Metal	49822	49823			

Rated voltage: 12V AC. IPX8 protection. Includes 2.5 m H07RN-F 2 x 1.5 mm² cable. Compatible with mini niche (not included). Select the appropriate option for each pool (see page 433).

According to UE Regulation 2019/2020, from September 1st, 2021 halogen cannot be sold anymore on the European Union market. This is also valid in other countries such as UK and Qatar.



Lamps

TECHNICAL FEATURES

Lamps for lights


Type of lamp		Code	Consumption
Halogen PAR56	For lights with niche	00370	300W (12 V)
Dichroic GX-5.3	For mini lights	19334	50W (12 V)

NICHES

Standard niches



TECHNICAL FEATURES

Niches				
Concrete pool	Prefabricated pools		Panels pool	
	With inserts	Without inserts	With inserts	Without inserts
00349 	00364	28887	23671	23670
	17805	72261		

Compatible with: LumiPlus FlexiNiche, LumiPlus PAR56 series, Standard and Global halogen lights and PAR56 Aquasphere projectors



AISI-316L stainless steel niches

TECHNICAL FEATURES


AISI-36 stainless steel niches	
Concrete pools	Liner swimming pool
54102	54103

Compatible with: LumiPlus FlexiNiche in Stainless Steel, LumiPlus stainless PAR56 steel range and stainless steel incandescent projectors.




PS niches

TECHNICAL FEATURES

PS niches		
Concrete pool	Prefabricated pools	
	With inserts	Without inserts
00355 	-	00367

Compatible with: LumiPlus FlexiNiche, Global and PAR56 Aquasphere projectors.






Niches for projector DESIGN

and also compatibles with LumiPlus FlexiNiche



TECHNICAL FEATURES

Niches			
Concrete pool	Prefabricated pools		Fixing kit for other niches
	With inserts	Without inserts	
59813 	59814	59815	59818*

Compatible with: LumiPlus FlexiNiche ABS and Stainless Steel and LumiPlus Design.


* Fitting kit to install LumiPlus Design to the majority of niches from Ø180 to Ø190 mm on the market (Hugo Lahme, MTS Productsts, Wibre...).



Mini niches



TECHNICAL FEATURES

MINI niches		
Concrete pool	Prefabricated pools	Panel pools
06967 	00369	49828


Compatible LumiPlus FlexiMini V1and V2; LumiPlus Mini V2 series and Mini halogen lights for niche.



Mini niche with integrated nozzle for fast assembly Mini projectors



TECHNICAL FEATURES

Mini niche with integrated nozzle for fast assembly Mini projectors	
Concrete pools	Prefabricated pools
53956 	59983

53956: Compatible with the LumiPlus FlexiMini V1 and V2; LumiPlus Mini V2; LumiPlus V3, LumiPlus FlexiRapid and Mini halogen snap-in ranges.

59983: Compatible with the LumiPlus FlexiMini V1 and V2; LumiPlus Mini V3 and LumiPlus FlexiRapid ranges.



Transformers for pool and fountain lighting



More compact.
More functional.
Specially designed for lighting up fountains and pools.

DESCRIPTION

- Suitable for all types of circuit board.
- Quick and easy installation.
- Connection via terminals protected against indirect contacts.
- Up to 40 m between the spotlight and transformer.
- Made in compliance with Standard UNE-EN-61558-2-6.
- IP-20 protection rating.
- Age-resistant housing.

	Code	Standard Pack	Standard weight in kg	Standard volume in m ³
100 VA 230 V to 12 V transformer	00383-1369	-	-	-
300 VA 230 V to 12 V transformer	00384-1369	-	-	-
600 VA 230 V to 12 V transformer	00385-1369	-	-	-



Transformers



DESCRIPTION

Made in compliance with standard EN 60742.

	Code	Standard Pack	Standard weight in kg	Standard volume in m ³
130VA from 230V to 12V	00383-4146	6	15.0	0.011
300VA from 230V to 12V cable length up to 35 m	71436	4	21.0	0.012
600VA from 230V to 12V cable length up to 25 m	00385-4146	2	19.0	0.012

Alternative transformer range, on enquiry.



Encapsulated security transformer with IP-65 protection rating for pools



DESCRIPTION

Manufactured according to the rules UNE-EN 61558 and directive CE.

- Bodywork has IP-657 protection rating.
- Class II transformer. Total protection against all electric shocks.
- Self-extinguishing bodywork, as per IEC 695-2-1
- Frequency of 50-60 Hz.

	Code	Standard Pack	Standard weight in kg	Standard volume in m ³
130 VA from 220-240 V to 12 V	35807	1	3.2	0.02
400 VA from 220-240 V to 12-17 V	35385	1	6.8	0.04
800 VA from 280-240 V to 12-17 V	35386	1	10.4	0.04

Transformer protection boxes



DESCRIPTION

Made of zinc plated steel plate, painted finish.


	Code	Standard Pack	Standard weight in kg	Standard volume in m ³
For transformer 00383	00386	1	1.15	0.01
For transformer 00384	00387	1	1.57	0.01
For transformer 00385	00388	1	3.00	0.01

Connection box with security cover



30825

30825CL090



30825CL129

30825CL144

DESCRIPTION

Manufactured in ABS, made up of three 3/4" inlets/outlets M-25 and 3/4" thread connections.

	Code	Standard Pack	Standard weight in kg	Standard volume in m ³
White	30825	12	4.65	0.030
Beige	30825CL090	12	4.65	0.030
Light Grey	30825CL129	12	4.65	0.030
Anthracite	30825CL144	12	4.65	0.030

Connection boxes for gluing pipes Ø50 mm



65215

65215CL090



65215CL129

65215CL144

	Code	Standard Pack	Standard weight in kg	Standard volume in m ³
White	65215	8	3.8	0.030
Beige	65215CL090	8	3.8	0.030
Light Grey	65215CL129	8	3.8	0.030
Anthracite	65215CL144	8	3.8	0.030

Connection box



DESCRIPTION

In AISI-316 stainless steel. Two PG 15 thread side outlets with two PG16 to M25 converters.

3/4" BSP threaded bottom connection.

	Code	Standard Pack	Standard weight in kg	Standard volume in m ³
Connection box	00393	1	0.21	0.002



Flexible conduit hose



DESCRIPTION

For connection from light to connection box, length 1 m hose.

	Code	Standard Pack	Standard weight in kg	Standard volume in m ³
Threaded ends 3/4" & M25	28138	1	-	-
M-25 socket joint	10892-0404	1	-	-
Threaded ends 3/4" and M26 150 cm	28138-150	1	-	-



Cable roll H07RN-F



	Code	Standard Pack	Standard weight in kg	Standard volume in m ³
Cable 2x1.5mm ² - 5m.	74652	1	-	0.01
Cable 2x1.5mm ² - 10m.	74656	1	-	0.01
Cable 2x1.5mm ² - 15m.	74657	1	-	0.01
Cable 2x1.5mm ² - 20m.	74658	1	-	0.01
Cable 2x1.5mm ² - 25m.	74659	1	-	0.01
Cable 2x1.5mm ² - 30m.	74673	1	-	0.01
Cable 2x2.5mm ² - 10m.	71645	1	-	0.01
Cable 2x2.5mm ² - 15m.	71646	1	-	0.01
Cable 2x2.5mm ² - 20m.	71647	1	-	0.01
Cable 2x2.5mm ² - 25m.	71648	1	-	0.01
Cable 2x2.5mm ² - 30m.	71649	1	-	0.01
100m cable roll	15264	1	187.5	-



Underwater connection kit



DESCRIPTION

The kit has all the necessary components to carry out any watertight connection. Due to the properties of the product, the resin seals all gaps. Maximum safety, easy installation, in 2 hours it is ready to be submerged.

	Code	Standard Pack	Standard weight in kg	Standard volume in m ³
Kit for Ø 13 to 15 mm cables	32803	1	0.3	0.002
Kit for Ø 8 to 12 mm cables	35661	1	0.3	0.002



Underwater connector

with IP68 protection rating and 4 poles



DESCRIPTION

Includes 5 connectors and two wrenches.

	Code	Standard Pack	Standard weight in kg	Standard volume in m ³
Overhead connector	71318	24	4.2	0.3

Aquarmony Loudspeaker



DESCRIPTION

With frontal installation. To listen to music and voice underwater creating a magical and different atmosphere. Aquarmony is a sealed waterproof loudspeaker designed for your pool. It is made of high quality components, innovative technology and with an assembly system assuring a correct operation in salt water or with a high Chlorine content. Easy installation.

	Code	Standard Pack	Standard weight in kg	Standard volume in m ³
Aquarmony Loudspeaker	25680	-	-	-
Niche for concrete pool	00349	-	-	-
Niche for liner pool	00364	-	-	-

Note: The niches come with a stuffing box assembly and a 1.5-m cable grommet specially designed for the Aquarmony range



TECHNICAL FEATURES

Maximum power	60 W
Impedance	4 ohm
Frequency	200-12000 Hz
Maximum area per loudspeaker	80 m ²
Maximum installation depth	40 cm
Weight	5 Kg
Cable length supplied	5 m

Amplifier and loudspeakers

RK400S



DESCRIPTION

- Built-in SELV power pack with all required protection ratings and safety systems.
- Fully insulated input and output ports, in compliance with standard ENV 61558-1 CEI EN 64-8/7, Section 702.
- RCA stereo input port compatible with any source (CD player, MP3 player, smartphone, etc.).
- Input and output XLR link for connecting other RK400-S devices together.
- Automated equalizers and limiters specially redesigned by Aquarmony.
- Automatic gain control, which does not require volume buttons.
- Four 60 W RMS amplifiers that work separately.
- Output through a gold-plated screw connector.
- On/off and signal display light.

	Code	Standard Pack	Standard weight in kg	Standard volume in m ³
Amplifier and loudspeakers	RK400S	1	-	-

TECHNICAL FEATURES

Maximum power	4 x 60 W rms
Impedance	4 ohm
Frequency	50-20,000 Hz
Weight	3.6 Kg

