

# Product datasheet

Specifications



## Reflex iC60N Ti24 40 A 3P curve B integrated control MCB

A9C61340

### Main

Device application	Control Distribution
Range	Acti9
Product name	Reflex iC60
Device short name	Reflex iC60N
Product or component type	Integrated control circuit breaker
Poles description	3P
Number of protected poles	3
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	B

### Complementary

[In] rated current	40 A
Network frequency	50/60 Hz
Breaking capacity code	N
Breaking capacity	20 kA Icu at 220...240 V AC 50/60 Hz conforming to EN/IEC 60947-2 10 kA Icu at 380...415 V AC 50/60 Hz conforming to EN/IEC 60947-2
[Ui] rated insulation voltage	500 V AC
Contact position indicator	Yes
Control type	Remote control by continuous command Remote control by pulse ON/OFF button Toggle
Control signal type	Maintained Impulse Maintained very low voltage
Local signalling	Green LED: device ON Flashing LED: device overheat Flashing LED: device tripped Flashing LED: device ready Red LED: fault
[Uc] control circuit voltage	230 V AC 50/60 Hz 24 V AC 50/60 Hz 48 V AC 50/60 Hz 24 V DC 48 V DC

<b>[Us] rated supply voltage</b>	230 V AC at 50/60 Hz
<b>Mounting mode</b>	Fixed
<b>Mounting support</b>	35 mm symmetrical DIN rail
<b>9 mm pitches</b>	11
<b>Height</b>	84 mm
<b>Width</b>	99 mm
<b>Depth</b>	77 mm
<b>Colour</b>	White
<b>Mechanical durability</b>	50000 cycles
<b>Electrical durability</b>	AC-1: 50000 cycles AC 50 Hz
<b>Provision for padlocking</b>	Padlockable
<b>Locking options description</b>	Padlock in OFF position
<b>Earth-leakage protection</b>	Separate block
<b>Product compatibility</b>	With PLC

## Environment

<b>IP degree of protection</b>	IP20 conforming to IEC 60529
<b>Pollution degree</b>	3
<b>Tropicalisation</b>	2
<b>Relative humidity</b>	93 % at 40 °C

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	9.0 cm
<b>Package 1 Width</b>	11.5 cm
<b>Package 1 Length</b>	17.0 cm
<b>Package 1 Weight</b>	733.0 g
<b>Unit Type of Package 2</b>	S03
<b>Number of Units in Package 2</b>	14
<b>Package 2 Height</b>	30.0 cm
<b>Package 2 Width</b>	30.0 cm
<b>Package 2 Length</b>	40.0 cm
<b>Package 2 Weight</b>	10.713 kg

## Offer Sustainability

<b>Sustainable offer status</b>	Green Premium product
<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
<b>Mercury free</b>	Yes
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
<b>RoHS exemption information</b>	Yes

---

<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>
<b>Circularity Profile</b>	<a href="#">End of Life Information</a>
<b>WEEE</b>	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
<b>Halogen content performance</b>	Halogen free plastic parts product

---

### **Contractual warranty**

---

<b>Warranty</b>	18 months
-----------------	-----------

### **Recommended replacement(s)**