



OMT1-IE3 355LY-4 355kW 400/690V 50Hz , . # AA3F4D5553T0CS

## DATASHEET

50Hz |

Frame type:	cast iron	Connection:	Δ/Y
Model:	OMT1-IE3	Run Capacitor:	
Output:	355 kW	Start Capacitor:	
Rated voltage:	400/690V	Rotor voltage:	
Frame:	355 mm	Rotor connection:	
Poles:	4	Rotor current:	
Frequency:	50 Hz	No load current:	
Rated speed:	1488 RPM	Insulation class:	F
Rated current:	598/346,7 A	Temp. rise:	80 K
Locked rotor current(Ia/In):	720%	Service factor:	1
Locked rotor torque(Ma/Mn):	220%	Duty:	S1
Breakdown torque(Ma/Mn):	290%	Amb. temp.:	-20~40 °C
Mounting:	B35	Altitude:	1000 m
Noise level:	79 dB	Protection:	IP55
Approx. weight:	2060 kg	Cooling:	IC411
Mom. of inertia:	11,3 kg/m <sup>2</sup>	Vibration:	2,8 mm/s
Slip:	0,8%	Dir. rotation:	BOTH
Rated torque:	2277 Nm	Starting method:	DIRECT ON LINE
		Coupling:	DIRECT
		Load type:	PARABOLIC CURVE

### PERFORMANCE

Output	50%	75%	100%
Efficiency(%):	93,1	96,1	96
Power factor:			0,89

### STANDARDS

Specification:	IEC60034-1/GB755
Test:	IEC60034-2/GB/T1032
Noise	IEC60034-9/GB10069.3
Vibration:	IEC60034-14/GB10068

### BEARING

	NDE	DE
Bearing	6320 C3	6322 C3
Regreasing int(h):	4000	4000
Grease amount(g):	50	60
Grease polyrexEM:	Caltex SRI-2	Caltex SRI-2

### ACCESSORIES

PTC 150°C

There may be differences between rating plate and calculated values