

SINGLE BLADE CLOSED IMPELLER - RANGE CS
SELECTION TABLE

Type	Power (KW)	Q (L/S)		Q (M3/hr.)		Head (m)		Outlet (Inch)	Free Passage (mm)
		From	Up to	From	Up to	From	Up to		
CS.80.75.2T	7.50	5.55	37.50	19.98	135.00	28.00	5.80	3 "	76 mm
CS.80.85.2T	8.50	5.55	38.88	19.98	139.97	32.00	11.00		76 mm
CS.80.95.2T	9.50	5.55	38.88	19.98	139.97	37.50	13.50		56 mm
CS.80.115.2T	11.50	5.55	38.88	19.98	139.97	41.50	19.00		56 mm
CS.80.25.4T	2.50	11.11	30.55	40.00	109.98	9.00	3.00		56 mm
CS.80.30.4T	3.00	11.11	31.95	40.00	115.02	10.50	3.50		56 mm
CS.100.25.4T	2.50	11.66	43.05	41.98	154.98	8.20	2.50		4 "
CS.100.35.4T	3.50	11.66	47.21	41.98	169.96	11.00	3.00	80 mm	
CS.100.45.4T	4.50	11.66	52.78	41.98	190.01	13.30	3.90	80 mm	
CS.100.52.4T	5.50	11.66	58.33	41.98	209.99	15.00	4.20	80 mm	
CS.100.11.6T	1.10	8.33	27.76	29.99	99.94	3.80	1.40	80 mm	
CS.100.15.6T	1.50	8.33	33.33	29.99	119.99	5.00	1.90	80 mm	
CS.100.17.6T	1.70	8.33	38.88	29.99	139.97	6.80	2.00	80 mm	
CS.150.30.4T	3.00	12.50	60.00	45.00	216.00	8.40	2.00	6 "	
CS.150.40.4T	4.00	12.50	66.11	45.00	238.00	10.50	2.30		100 mm
CS.150.55.4T	5.50	12.50	78.05	45.00	280.98	13.50	2.30		95 mm
CS.150.75.4T	7.50	12.50	83.88	45.00	301.97	17.50	4.40		108 mm
CS.150.150.4T	15.00	12.50	93.33	45.00	335.99	20.00	6.40		95 mm
CS.150.185.4T	18.50	12.50	116.66	45.00	419.98	24.30	11.00		108 mm