

Submittal Data

PROJECT:	UNIT TAG:	QUANTITY:
REPRESENTATIVE: _____	TYPE OF SERVICE:	DATE: _____
ENGINEER:	SUBMITTED BY:	DATE:
CONTRACTOR:	APPROVED BY:	DATE:
	ORDER NO.:	DATE:




CRN 10-5 A-FGJ-A-E-HQQE


Vertical, multistage centrifugal pump with suction and discharge ports on the same level. Pump materials in contact with the liquid are in high-grade stainless steel (EN 1.4401)

Note! Product picture may differ from actual product

Conditions of Service	Pump Data	Motor Data
Liquid: Water	Max pressure at stated temp: 25 bar / 120 °C	Rated power - P2: 2.2 kW
Temperature: 20 °C	Liquid temperature range: -20 .. 120 °C	Rated voltage: 220-240D/380-415Y V
Specific Gravity: 1.000	Maximum ambient temperature: 60 °C	Mains frequency: 50 Hz
	Shaft seal: HQQE	Enclosure class: IP55 Dust/Jetting
	Product number: On request	Insulation class: F
		Motor protection: NONE
		Motor type: 90LE
		Eta 1/1: 85.9 %



Submittal Data




Materials:

Base:	Stainless steel EN 1.4408 AISI 316
Impeller:	Stainless steel AISI 316 EN 1.4401
Material code:	A
Code for rubber:	E



Project:
Reference Number:

Client:
Client Number:
Contact:

Qty.	Description
1	CRN 10-5 A-FGJ-A-E-HQQE  Note! Product picture may differ from actual product Product No.: On request Vertical, multistage centrifugal pump with inlet and outlet ports on same the level (inline). Pump materials in contact with the liquid are in high-grade stainless steel. A cartridge shaft seal ensures high reliability, safe handling, and easy access and service. Power transmission is via a rigid split coupling. Pipe connection is via combined DIN-ANSI-JIS flanges. The pump is fitted with a 3-phase, fan-cooled asynchronous motor. Further product details Steel, cast iron and aluminium components have an epoxy-based coating made in a cathodic electro-deposition (CED) process. CED is a high-quality dip-painting process where an electrical field around the products ensures deposition of paint particles as a thin, well-controlled layer on the surface. An integral part of the process is a pretreatment. The entire process consists of these elements: 1) Alkaline-based cleaning. 2) Zinc phosphating. 3) Cathodic electro-deposition. 4) Curing to a dry film thickness 18-22 my m. The colour code for the finished product is NCS 9000/RAL 9005. Pump A standard split coupling connects the pump and motor shaft. It is enclosed in the pump head/motor stool by means of two coupling guards.  The pump head and flange for motor mounting is made in one piece (cast iron). The pump head cover is a separate component (stainless steel). The pump head has a combined 1/2" priming plug and vent screw.

Project:
Reference Number:

Client:
Client Number:
Contact:

Qty.	Description
1	 The pump is fitted with a balanced O-ring seal unit with a rigid torque-transmission system. This seal type is assembled in a cartridge unit which makes replacement safe and easy. Due to the balancing, this seal type is suitable for high-pressure applications. The cartridge construction also protects the pump shaft from possible wear from a dynamic O-ring between pump shaft and shaft seal. Seal faces: - Rotating seal ring material: silicon carbide (SiC) - Stationary seat material: silicon carbide (SiC) This material pairing is used where higher corrosion resistance is required. The high hardness of this material pairing offers good resistance against abrasive particles. Secondary seal material: EPDM (ethylene-propylene rubber) EPDM has excellent resistance to hot water. EPDM is not suitable for mineral oils.  The shaft seal is screwed into the pump head. The chambers and impellers are made of stainless-steel sheet. The chambers are provided with a PTFE neck ring offering improved sealing and high efficiency. The impellers have smooth surfaces, and the shape of the blades ensure a high efficiency. The pump has a stainless steel base mounted on a separate base plate. This base and base plate are kept in position by the tension of the staybolts which hold the pump together. The outlet side of the base has a combined drain plug and bypass valve. The pump is secured to the foundation by four bolts through the base plate. The flanges and base are cast in one piece and prepared for connection by means of DIN, ANSI or JIS. Motor The motor is a totally enclosed, fan-cooled motor with principal dimensions to IEC and DIN standards. The motor is flange-mounted with tapped-hole flange (FT). Motor-mounting designation in accordance with IEC 60034-7: IM B 14 (Code I) / IM 3601 (Code II). Electrical tolerances comply with IEC 60034. The motor efficiency is classified as IE3 in accordance with IEC 60034-30-1. The motor does not incorporate motor protection and must be connected to a motor-protective circuit breaker which can be manually reset. The motor-protective circuit breaker must be set according to the rated current of the motor (I1/I1). The motor can be connected to a variable speed drive for adjustment of pump performance to any duty point. Grundfos CUE offers a range of variable speed drives. Please find more information in Grundfos Product Center. Technical data Liquid:



Company name: ALMAWARED ENGINEERING AND TRADING S.A.E.

Created by: Eng. Mohamed Yousry

Phone: 01223033988

Email: mohamed.yousry@met-eg.com

Date:

Project:

Reference Number:

Client:

Client Number:

Contact:

Qty.	Description
1	Pumped liquid: Water Liquid temperature range: -20 .. 120 °C Selected liquid temperature: 20 °C Density: 998.2 kg/m³ Technical: Pump speed on which pump data are based: 2899 rpm Rated flow: 10 m³/h Rated head: 40.7 m Pump orientation: Vertical Shaft seal arrangement: Single Primary shaft seal: HQQE Code for shaft seal: HQQE Approvals: CE,EAC,UKCA,SEPRO,RCM, Approvals for drinking water: WRAS,ACS Curve tolerance: ISO9906:2012 3B Materials: Type key, code for materials: A Type key, code for rubber components. E = EPDM, V=FKM: E Base: Stainless steel EN 1.4408 AISI 316 Impeller: Stainless steel EN 1.4401 AISI 316 Bearing: SIC Installation: Maximum ambient temperature: 60 °C Maximum operating pressure: 25 bar Max pressure at stated temp: 25 bar / 120 °C 25 bar / -20 °C Type of connection: DIN / ANSI / JIS Size of inlet connection: DN 40 1 1/2 inch Size of outlet connection: DN 40 1 1/2 inch Pressure rating for connection: PN 25 Flange rating inlet: 300 lb Flange size for motor: FT115 Terminal box position: 6 Electrical data: Motor standard: IEC Motor type: 90LE Rated power - P2: 2.2 kW



Company name: ALMAWARED ENGINEERING AND TRADING S.A.E.
Created by: Eng. Mohamed Yousry
Phone: 01223033988
Email: mohamed.yousry@met-eg.com
Date:

Project:
Reference Number:


Client:
Client Number:
Contact:

Qty.	Description
1	Power (P2) required by pump: 2.2 kW Mains frequency: 50 Hz Rated voltage: 3 x 220-240D/380-415Y V Rated current: 8.00/4.60 A Starting current: 840-920 % Cos phi - power factor: 0.86-0.80 Rated speed: 2890-2910 rpm IE Efficiency class: IE3 Motor efficiency at full load: 85.9 % Motor efficiency at 3/4 load: 88.2-87.2 % Motor efficiency at 1/2 load: 88.0-85.5 % Number of poles: 2 Enclosure class (IEC 34-5): IP55 Dust/Jetting Insulation class (IEC 85): F Motor No: 85U01908 Controls: Terminal box position: 6 Frequency converter: None Others: Minimum efficiency index, MEI $\geq$: 0.70 Net weight: 50 kg Gross weight: 54 kg Shipping volume: 0.104 m³ Country of origin: DK Custom tariff no.: 84137000


Project:
Reference Number:

Client:
Client Number:
Contact:

On request CRN 10-5 A-FGJ-A-E-HQQE 50 Hz




Pumped liquid = Water
 Liquid temperature during operation = 20 °C
 Density = 998.2 kg/m³






Project:
Reference Number:

Client:
Client Number:
Contact:

Description	Value
General information:	
Product name:	CRN 10-5 A-FGJ-A-E-HQQE
Product No:	On request
EAN number:	On request
Technical:	
Pump speed on which pump data are based:	2899 rpm
Rated flow:	10 m ³ /h
Rated head:	40.7 m
Maximum head:	51.1 m
Stages:	5
Impellers:	5
Number of reduced-diameter impellers:	0
Low NPSH:	N
Pump orientation:	Vertical
Shaft seal arrangement:	Single
Primary shaft seal:	HQQE
Code for shaft seal:	HQQE
Approvals:	CE,EAC,UKCA,SEPRO,R CM,
Approvals for drinking water:	WRAS,ACS
Curve tolerance:	ISO9906:2012 3B
Pump version:	A
Model:	A
Materials:	
Type key, code for materials:	A
Type key, code for rubber components. E = EPDM, V=FKM:	E
Base:	Stainless steel EN 1.4408 AISI 316
Impeller:	Stainless steel EN 1.4401 AISI 316
Material code:	A
Code for rubber:	E
Bearing:	SIC
Installation:	
Maximum ambient temperature:	60 °C
Maximum operating pressure:	25 bar
Max pressure at stated temp:	25 bar / 120 °C 25 bar / -20 °C
Type key, code for pipework connection:	FGJ
Type of connection:	DIN / ANSI / JIS
Size of inlet connection:	DN 40 1 1/2 inch
Size of outlet connection:	DN 40 1 1/2 inch
Pressure rating for connection:	PN 25
Flange rating inlet:	300 lb
Flange size for motor:	FT115
Terminal box position:	6
Connect code:	FGJ
Liquid:	
Pumped liquid:	Water



Pumped liquid = Water
 Liquid temperature during operation = 20 °C
 Density = 998.2 kg/m³





Company name: ALMAWARED ENGINEERING AND TRADING S.A.E.
Created by: Eng. Mohamed Yousry
Phone: 01223033988
Email: mohamed.yousry@met-eg.com
Date:

Project:
Reference Number:


Client:
Client Number:
Contact:

Description	Value
Liquid temperature range:	-20 .. 120 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m³
Electrical data:	
Motor standard:	IEC
Motor type:	90LE
Rated power - P2:	2.2 kW
Power (P2) required by pump:	2.2 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 220-240D/380-415Y V
Rated current:	8.00/4.60 A
Starting current:	840-920 %
Cos phi - power factor:	0.86-0.80
Rated speed:	2890-2910 rpm
IE Efficiency class:	IE3
Motor efficiency at full load:	85.9 %
Motor efficiency at 3/4 load:	88.2-87.2 %
Motor efficiency at 1/2 load:	88.0-85.5 %
Number of poles:	2
Enclosure class (IEC 34-5):	IP55 Dust/Jetting
Insulation class (IEC 85):	F
Built-in motor protection:	NONE
Motor No:	85U01908
Controls:	
Terminal box position:	6
Frequency converter:	None
Others:	
Minimum efficiency index, MEI ≥:	0.70
Net weight:	50 kg
Gross weight:	54 kg
Shipping volume:	0.104 m³
Country of origin:	DK
Custom tariff no.:	84137000

Project:
Reference Number:

Client:
Client Number:
Contact:


On request CRN 10-5 A-FGJ-A-E-HQQE 50 Hz



Project:
Reference Number:

Client:
Client Number:
Contact:

On request CRN 10-5 A-FGJ-A-E-HQQE 50 Hz




Note! All units are in [mm] unless others are stated.
 Disclaimer: This simplified dimensional drawing does not show all details.


Project:
Reference Number:

Client:
Client Number:
Contact:

On request CRN 10-5 A-FGJ-A-E-HQQE 50 Hz



Note! All units are in [mm] unless others are stated.



Project:
Reference Number:

Client:
Client Number:
Contact:

Order Data:

Position	Your pos.	Product name	Amount	Product No	Total
		CRN 10-5 A-FGJ-A-E-HQQE	1	On request	