



Figure similar

General information	
Product type designation	AQ 8xU/I HS
HW functional status	from FS01
Firmware version	V2.1.0
• FW update possible	Yes
Product function	
• I&M data	Yes; I&M0 to I&M3
• Isochronous mode	Yes
• Prioritized startup	No
• Output range scalable	No
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	V14 / -
• STEP 7 configurable/integrated from version	V5.5 SP3 / -
• PROFIBUS from GSD version/GSD revision	V1.0 / V5.1
• PROFINET from GSD version/GSD revision	V2.3 / -
Operating mode	
• Oversampling	Yes
• MSO	Yes
CiR - Configuration in RUN	
Reparameterization possible in RUN	Yes
Calibration possible in RUN	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption, max.	320 mA; with 19.2 V supply
Power	
Power consumption from the backplane bus	1.15 W
Power loss	
Power loss, typ.	7 W
Analog outputs	
Number of analog outputs	8
Voltage output, short-circuit protection	Yes

Voltage output, short-circuit current, max.	45 mA
Current output, no-load voltage, max.	20 V
Cycle time (all channels), min.	125 µs; independent of number of activated channels
Output ranges, voltage	
• 0 to 10 V	Yes
• 1 V to 5 V	Yes
• -5 V to +5 V	No
• -10 V to +10 V	Yes
Output ranges, current	
• 0 to 20 mA	Yes
• -20 mA to +20 mA	Yes
• 4 mA to 20 mA	Yes
Connection of actuators	
• for voltage output two-wire connection	Yes
• for voltage output four-wire connection	Yes
• for current output two-wire connection	Yes
Load impedance (in rated range of output)	
• with voltage outputs, min.	1 kΩ
• with voltage outputs, capacitive load, max.	100 nF
• with current outputs, max.	500 Ω
• with current outputs, inductive load, max.	1 mH
Cable length	
• shielded, max.	200 m
Analog value generation for the outputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit
• Conversion time (per channel)	50 µs; independent of number of activated channels
Settling time	
• for resistive load	30 µs; see additional description in the manual
• for capacitive load	100 µs; see additional description in the manual
• for inductive load	100 µs; see additional description in the manual
Errors/accuracies	
Output ripple (relative to output range, bandwidth 0 to 50 kHz), (+/-)	0.02 %
Linearity error (relative to output range), (+/-)	0.15 %
Temperature error (relative to output range), (+/-)	0.002 %/K
Crosstalk between the outputs, max.	-100 dB
Repeat accuracy in steady state at 25 °C (relative to output range), (+/-)	0.05 %
note regarding accuracy	at temperatures below 0 °C, the figures for operating error and temperature error are doubled
Operational error limit in overall temperature range	
• Voltage, relative to output range, (+/-)	0.3 %
• Current, relative to output range, (+/-)	0.3 %
Basic error limit (operational limit at 25 °C)	
• Voltage, relative to output range, (+/-)	0.2 %
• Current, relative to output range, (+/-)	0.2 %
Isochronous mode	
Execution and activation time (TCO), min.	100 µs
Bus cycle time (TDP), min.	250 µs
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Substitute values connectable	Yes
Alarms	
• Diagnostic alarm	Yes
Diagnoses	
• Monitoring the supply voltage	Yes
• Wire-break	Yes; Only for output type "current"
• Short-circuit	Yes; Only for output type "voltage"
• Overflow/underflow	Yes

Diagnostics indication LED			
• RUN LED		Yes; green LED	
• ERROR LED		Yes; red LED	
• Monitoring of the supply voltage (PWR-LED)		Yes; green LED	
• Channel status display		Yes; green LED	
• for channel diagnostics		Yes; red LED	
• for module diagnostics		Yes; red LED	
Potential separation			
Potential separation channels			
• between the channels		No	
• between the channels, in groups of		8	
• between the channels and backplane bus		Yes	
• Between the channels and load voltage L+		Yes	
Permissible potential difference			
between S- and MANA (UCM)		8 V DC	
Isolation			
Isolation tested with		707 V DC (type test)	
Standards, approvals, certificates			
Siemens Eco Profile (SEP)		Siemens EcoTech	
Suitable for safety-related tripping of standard modules		Yes; from FS04	
Ecological footprint			
• environmental product declaration		Yes	
Global warming potential			
— global warming potential, (total) [CO2 eq]		37.6 kg	
— global warming potential, (during production) [CO2 eq]		11.1 kg	
— global warming potential, (during operation) [CO2 eq]		26.8 kg	
— global warming potential, (after end of life cycle) [CO2 eq]		-0.364 kg	
Highest safety class achievable for safety-related tripping of standard modules			
• Performance level according to ISO 13849-1		PL d	
• Category according to ISO 13849-1		Cat. 3	
• SIL acc. to IEC 62061		SIL 2	
• remark on safety-oriented shutdown		https://support.industry.siemens.com/cs/de/en/view/39198632	
Security			
signed firmware update		No	
data integrity		No	
Ambient conditions			
Ambient temperature during operation			
• horizontal installation, min.		-30 °C; From FS03	
• horizontal installation, max.		60 °C	
• vertical installation, min.		-30 °C; From FS03	
• vertical installation, max.		40 °C	
Altitude during operation relating to sea level			
• Installation altitude above sea level, max.		5 000 m; Restrictions for installation altitudes > 2 000 m, see manual	
Dimensions			
Width		35 mm	
Height		147 mm	
Depth		129 mm	
Weights			
Weight, approx.		325 g	
Classifications			
		Version	Classification
	eClass	14	27-24-22-01
	eClass	12	27-24-22-01
	eClass	9.1	27-24-22-01
	eClass	9	27-24-22-01

eClass	8	27-24-22-01
eClass	7.1	27-24-22-01
eClass	6	27-24-22-01
ETIM	10	EC001420
ETIM	9	EC001420
ETIM	8	EC001420
ETIM	7	EC001420
IDEA	4	3562
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval




[Miscellaneous](#)
[Manufacturer Declaration](#)

[Metrological Approval](#)

General Product Approval

For use in hazardous locations

[KC](#)


[FM](#)

[FM](#)

For use in hazardous locations

Maritime application

[CCC-Ex](#)


[Type Examination Certificate](#)
[Miscellaneous](#)


Maritime application




[NK / Nippon Kaiji Kyokai](#)



Maritime application

Environment

[CCS \(China Classification Society\)](#)




last modified:

10/23/2025 